# Dust extractors for dental lab

## emeritalia















Emeritalia manufactures vacuum cleaners for dental technician benches and goldsmith's laboratories, compatible with any type of equipment used and integrable to the workstation in over-counter or under-counter mode. The high power combined with the low noise level of Emeritalia's vacuum cleaners ensure greater work efficiency and the highest standards of cleanliness and safety, thanks to the punctual suction and multilayer filtering of dust generated during processing.



EMERITALIA s.r.l., CF-P.IVA 07729220967, REA-MB1882144

Via Euclide 2, 20864 Agrate Brianza (MB) - Italy


www.emeritalia.it

produzione@emeritalia.it - Phone 0392027658, 0392027659



Practicality of use: LABÒ vacuum cleaners are extremely immediate to connect (by Plug&Play connection), operate, clean and maintain. They are equipped with EMC control, which automatically manages start/stop phases and as weel suction power.

Powerful, quiet, clean: LABÒ vacuum cleaners are extremely powerful while being surprisingly quiet at the same time. Absolute cleanliness is ensured by a multi-level filtration system.



- IMAGES FOR ILLUSTRATIVE PURPOSES ONLY - The company reserves the right to change aesthetic and technical features without notice

-low scheme

**Multilayer filtration** 

Microfiber bag M class FN60335.2.6 Large quantities of milling and fine powders put quickly your extraction unit and your device unit in critical conditions: they must be removed quickly and effectively. LABÒ 4.0 ALL removes dust and the highly effective filtering system reliably picks it up.

Thanks to the new design, the unit can be used in DUAL USE, with bag or in bagless mode.

The new interface ensures the connection to CAM system or to traditional device at 230V.

For the toughest jobs, The LABO 4 ALL is available also with BRUSHLESS motor type.



EXHAUST FILTER

M class washable diffusor to slow down and filter the exhaust before its emission into workplace



MOTOR REPLACEMENT


To keep the service simple and cost-effective.
With a simple operation you can replace motor by your self



FILTERING SYSTEM

The dust collector box can be used in double mode: BAG version or BAGLESS version

### INTERFACE CABLES









Labò 4.0 All

Labò 4.0 All BL

220/240 (110/120)	220/240 (110/120)
1.000	1.000
50	50
2.400	2.400
Brush	Brushless
EMC	EMC
Dual mode bag/bagless	Dual mode bag/bagless
M class (EN 60335-2-69)	M class (EN 60335-2-69)
M class (EN 60335-2-69)	M class (EN 60335-2-69)
Yes	Yes
RJ45 - CAM/power tool socket	RJ45 - CAM/power tool socket
< 59dB (A)	< 59dB (A)
235 × 550 × 530	235 x 550 x 530
18	18

Voltage Volt

Power

Flow rate

Depression

Engine technology

Operating mode

Filter technolog

Primer filter quality

Output filte quality

Filter cleaning

> Service port

(max)

Dimensions mm

> Weight kg

Large quantities of milling and fine powders put quickly your CAM unit in critical condition: they must be removed quickly and effectively.

LABÒ CAM vacuums remove dust from milling machine and the highly effective filtering system reliably picks it up.

Connecting the vacuum to the CAM unit. The interface connection ensures that the CAM unit and the vacuum device communicate perfectly to automatically manage start and stop. For the toughest jobs, the LABÒ CAM is also available with brushless motor.



### INTERFACE CABLES

3 4	3 4	4 1	6 1	2	3
Imes Core	AG	VHF - 4 pin	VHF - 6 pin	Sirona	Roland
6+/5 GND	6+/5 GND	6+/5 GND	6+/5 GND	6+/5 GND	6+/5 GND
4+/3 GND	3+/4 GND	1+/4 GND	1+/6 GND	2+/11 GND	1+/2 GND









Labò CAM	Labò CAM BL	Labò 3 CAM	Labò 3 CAM BL
220/240	220/240	220/240	220/240
900	800	900	800
45	41	45	41
2.100	2.000	2.100	2.000
Brush	Brushless	Brush	Brushless
EMC	EMC	EMC	EMC
M Class bag	M Class bag	M Class bag	M Class bag
M Class	M Class	M Class	M Class
E12	E12	E12	E12
Automatic	Automatic	Automatic	Automatic
RJ45	RJ45	RJ45	RJ45
< 59dB (A)	< 59dB (A)	< 59dB (A)	< 59dB (A)
250 × 500 × 370 250 × 500 × 370		250 x 500 x 370	250 × 500 × 370
13	13	13	13

Voltage Volt

Power

Flow rate

Depression

Engine technolog

Operating

Filter technolog

Primer filter quality

Output filter

Filter cleaning

interface

Noise leve (max)

Dimensions

Weight ka

VALVE

3-way valve with selector

completed with 2 hoses

All models

The best vacuum cleaner for workbenches and equipment for every modern dental and goldsmith laboratory.

LABÒ vacuum cleaners effectively remove dust from equipment, and the highly efficient filtering system reliably captures it.

Connectable to all devices thanks to EMC control that handles automatic and/or manual startup. Equipped with suction power regulator and filter shaker (according to model) to preserve the motor filter protection. Front door for quick maintenance and/or filter replacement.



# OPTIONALS REMOTE CONTROL FOOT PEDAL

Remote Foot switch control kit for starting

Labò 2 ECMM + Labò Brushless

\_\_\_\_\_

Labò Brushless









Labò 2 ECMM	Labò 2 DS	Labò 3 DS	Labò Brushless
220/240	220/240	220/240	220/240
900	900	900	800
45	45	45	41
2.100	2.100	2.100	2.000
Brush	Brush	Brush	Brushless
EMC	EMC	EMC	
M class bag	M class bag	M class bag	M class bag
M class	M class	M class	M class
E12	E12	E12	E12
	Manual & automatic	Manual & automatic	
Yes	Yes	Yes	
< 59dB (A)	< 59dB (A)	< 59dB (A)	< 59dB (A)
250 x 500 x 370	250 x 500 x 370	250 x 500 x 370	250 x 500 x 370
13	13	13	13

Voltage Volt

Power

Flow rate

Depression

Engine technolog

Operating mode

Filter technology

Primer filter quality

Output filte quality

Filter cleaning

Power too socket

Noise leve (max)

Dimensions

Weigh ka

Depression



PV 502

Compact and adaptable dust collector with high suction power and excellent dust retention. Adjustable suction power and automatic start and stop by EMC control device.

220 - 240

600

41

1.800

Brush

**EMC** 

M class bag F7 class filter

Yes

< 65dB (A)

220 x 250 x 270

4



BD 315

Dust collector suitable for dry and wet materials. High suction power and large (27lt.) dust container. Triple filtering system in Class M. Manual and automatic filter cleaning. Automatic start and stop by EMC control device.

220 - 240

1.200

70

2.400

Brush

**EMC** 

M class bag & filter

Yes

< 70 dB (A)

300 x 400 x 500

10.5



LABO DUST

The non-tip and non-slip grinding and extractor box protects against splinters, dust and fumes. With compressed air gun. **FEATURES** 

- Extraction directly at the object ensures a clear view
- · Maximum freedom of movement thanks to a large internal volume
- LED Technology for best contour and detail recognition



LABO AIR

Robust beech wood clamp. Variable and individual connection of the suction hose to the right or to the left ED 32 mm / ID 29 mm. **FEATURES** 

- Large protective plexiglass screen (130 x 260 mm)
- Secure fixing on workbenches with a thickness from 20 to 35 mm
- · A vailable also with LED lamp